





J-Curve Slim Line Array

The high-frequency speaker array is comprised of 10 small-diameter 1.5" speakers. By adopting a J-curve array configuration, the high-frequency unit achieves vertical coverage of 30 ° across a span of 170 °. With such a long, 10-driver array design the STAGEPAS 1K mkII can deliver clear, high quality sound consistently over longer distances, projecting uniform, high-quality sound from the front to the rear of the audience.



Class-leading 12-inch "compact" subwoofer

Despite housing a 12-inch speaker unit that is the largest in its class, the STAGEPAS 1K mkll boasts the smallest cabinet on the market for a subwoofer of this size and power. By incorporating Yamaha's own Twisted Flare


Port[™] technology to reduce port wind noise that can occur with compact bass-reflex subwoofers, the low-end output is maximized, producing very deep, powerful, distortion-free bass.



1100W amplifier

Also at the top of its class for output power, the 1100W Class-D amplifier module is capable of delivering an impressive 125 dB SPL from the deceptively compact speaker cabinet. And just as importantly, we've leveraged Yamaha's decades-long experience as a manufacturer of professional PA products, and innovator of related technologies to ensure that with great power comes great stability, and that the STAGEPAS 1K mkll maintains the same accurate, superior-quality sound even at high output.





Digital mixer with versatile input

With outstanding flexibility for a PA system of this size, the 5-channel digital mixer features three channels of mono microphone/line inputs and stereo inputs, with two of the mono input channels equipped with Hi-Z connectivity for direct input of acoustic-electric guitars and other instruments. In addition to Phone and 1/8" mini jacks, the stereo connections support playback with Bluetooth devices as well as a wide range of input sources from instruments to CDs, PCs and smartphones.



Professional control with a single knob

STAGEPAS 1K mkll comes equipped with a wealth of sound shaping functions, including 1-knob EQ for optimized multi band EQ setting, industry standard SPX reverb, and the "Mode" control for master output compression settings that match various applications such as "Speech" or "Music." Each of these functions can be set via a single knob, and have simplified many of the tough tasks like EQ and compression to get you great sound fast.



STAGEPAS Controller

With an all-new interface, STAGEPAS Controller is a dedicated remote control application for the STAGEPAS 1K mkll that allows users to adjust volume and 1-knob EQ or 4-band PEQ via Bluetooth during rehearsal or performance. You can also save the adjusted settings for certain songs or applications in order to shorten your setup process in the future and maintain consistency from one performance to the next, and even control the volume of multiple STAGEPAS 1K mkll units from within the application.

Additionally, STAGEPAS 1K mkll features a "Priority Ducker" can be turned on/off directly from the device.









* STAGEPAS Controller can be downloaded from Apple's App Store and Google Play at no charge. (Apple, iPhone and iPod are trademarks of Apple Inc., registered in the U.S and other countries. App Store is a service mark of Apple Inc. Android and Google Play are trademarks of Google Inc.).



Simple setup

Simply affix the 2 spacers and speaker unit into the subwoofer and setup is essentially done, with no cables, speaker stand, or additional gear required beyond the main unit. All you need is in the package.



Expandable STAGEPAS systems

Linking two STAGEPAS 1K mkll or a STAGEPAS 1K mkll with a DXL1K provides greater coverage area and increased output power for large-scale performances. Both stereo and mono playback are supported, and when set to mono, the inputs of the two linked units(*) can still be used.



- 2x STAGEPAS 1K mkll: up to six mono inputs plus two stereo inputs
- STAGEPAS 1K mkll and DXL1K:
 up to five mono inputs plus one stereo input

Fitted cover included

The STAGEPAS 1K mkII comes with its own cover which, in addition to protecting the unit, has pouches for both spacers and speaker array as well as additional storage for accessories to further streamline system setup and teardown.




Optional dolly (DL-SP1K)

An optional dedicated dolly allows for more convenient transportation — particularly useful for performers transporting additional gear and instruments. Featuring a simple, sturdy mechanism that locks down the speaker cover the lightweight dolly enables smooth, reliable transportation.




Application Examples


Mobile DJ




Guitar and vocals



Ensemble performance



Public speaking



Specifications

Main Specifications		
System Type		Powered subwoofer with a line array speaker
Frequency Response (-10 dB)		37 Hz - 20 kHz
Coverage Angle (Horizontal x Vertical)		170° x 30°
Crossover Frequency		240 Hz
Maximum Output Level (Measured peak,IEC noise@1m)		125 dB SPL
Power Requirements		Depending on area of purchase:
		100V 50Hz/60Hz, 110V-120V 60Hz, 220-240V 50/60Hz
Power Consumption		25 W (Idle), 91 W (1/8 power)
Dimensions (W x H x D)		System (maximum) 334 × 2,000 × 418 mm / 13.2 " × 78.7" × 16.5"
Weight		23.0 kg (50.7 lbs)
Mixer section		
The number of Mixing Channels		5
Analog Inputs		Mono mic/line x 3 + mono line x 2, stereo line x1
		LINK IN (MONO)
Bluetooth Audio Inputs		A2DP (SBC,AAC)
State Country and State Countr	Content Protection Method	SCMS-T
	Bluetooth Version	Ver 5.0
	Transmission Frequencies	2,402–2,480MHz
	Wireless Output	Class 1
	Maximum Wireless Output Power (EIRP)	15dBm (32mW)
Channel Functions	maximum vinoisse surpar i siroi (Emir)	Hi-Z switch : CH2/3
EQ / Effects		1-knob EQ : ALL channels
LQ / LIIGUIS		MODE (SPEECH/MUSIC/CLUB)
		4 types of reverb (HALL/PLATE/ROOM/ECHO) : CH1-3
Outputs		LINK OUT (MONO/R)
Outputs		MONITOR OUT (MONO)
External Controls		Reverb foot switch
		STAGEPAS Controller (iOS/Android app)
Amplifier section		STAGETAS CONTROLLE (105/Alliatola app)
		Class-D
Type Rated Output		1100W
		1100W
Speaker section		Line array angular - England
Enclosure		Line array speaker : Enclosed
Casalor Unit		Subwoofer: Bass-reflex type
Speaker Unit		Line array speaker: 1.5" (3.8 cm) Cone x10
Dimensions (W x H x D)		Subwoofer: 12" (30 cm) Cone
		Line array speaker : 67 × 582 × 86 mm / 2.6" × 22.9" × 3.4"
		Spacer (each): 67 × 555 × 86 mm / 2.6" × 21.9" × 3.4"
W-:-Li		Subwoofer: 334 × 550 × 418 mm / 13.2" × 21.7" × 16.5"
Weight		Line array speaker : 1.8 kg (4.0 lbs)
		Spacer (each) : 0.6 kg (1.3 lbs)
		Subwoofer : 20.0 kg (44.1 lbs)
Accessories		
Included in the package		Power cord, Cover, Owner's Manual
Optional accessories		DL-SP1K (dedicated dolly) / FC5 (foot switch for reverb ON/OFF)

Optional Accessories







STAGEPAS Controller

STAGEPAS 1K mkll's dedicated remote control application iOS/Android compatible

10



*Please visit our Web site for the latest information (http://www.yamahaproaudio.com/)







@yamaha_proaudio_official

